

#3

PATENT
Attorney Docket No. 97-060A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Reissue Application of:

LePage, et al.

Group Art Unit: 3623

Serial No. 09/205,318
(Re-issue of U.S. Patent 5,579,820)

Examiner: _____

Filed: 12/3/98
Accorded filing date: 12/4/98

For: ROLL-UP DOOR FOR VEHICLE
SHELTERS

RECEIVED

FEB 08 1999

OFFICE OF PETITIONS
A/C PATENTS

PETITION PURSUANT TO 37 C.F.R. §1.10 TO ACCORD
THE APPLICATION A CORRECTED FILING DATE
and
REQUEST FOR CORRECTED FILING RECEIPT

Assistant Commissioner
for Patents
Washington, D.C. 20231

Dear Sir:

Authorization to charge the \$130 for consideration of this petition to Deposit
Account 18-1450 is hereby granted.

This is a Petition pursuant to 37 C.F.R. §1.10 (c) to accord correspondence (in this case the original filing of the above-identified re-issue application) a filing date as of the "date in" on the "Express Mail" mailing label. The undersigned practitioner personally hand filed the subject application with the United States Postal Service on December 3, 1998. As reflected in the true copy of the "Express Mail" mailing label attached at Exhibit A, the "date in" box clearly shows the date of 12/3/98 (i.e., December 3, 1998).

In re LePage, et al.
Serial No. 09/205,318

Furthermore, as the true copy of the application filing paper (attached hereto as Exhibit B) clearly shows, the correspondence did include the "Express Mail" mailing label number of EI847855273US, and identified the date of deposit of 12/3/98. The "Express Mail" mailing label number appears on the re-issue application cover sheet (in the Certificate of Express Mail), on the re-issue application transmittal form, and on the return receipt postcard.

Applicants, through the undersigned attorney, became aware of the Patent Office having accorded this application an improper filing date upon receipt by the undersigned attorney of the filing receipt on or about January 19, 1999. This petition is being filed promptly on February 8, 1999.

Accordingly, it is submitted that all of the requirements of 37 C.F.R. §1.10 (c) for according this correspondence a filing date as of the "date in" on the "Express Mail" mailing label have been met, specifically:

(1) This petition is being filed promptly after the person (i.e., the undersigned attorney) became aware that the Patent Office accorded a filing date other than the U.S.P.S. deposit date;

(2) The number of the "Express Mail" mailing label was placed on the paper(s) that constitute the correspondence prior to the original mailing by "Express Mail"; and

(3) This petition includes (at Exhibit A) a true copy of the "Express Mail" mailing label showing the "date-in," to show the date of deposit.

Accordingly, it is respectfully requested that this application be accorded a filing date of December 3, 1998.


In re LePage, et al.
Serial No. 09/205,318

It is also respectfully requested that a corrected filing receipt indicating the appropriate filing date be issued. Toward that end, the undersigned attorney would also note several errors in the filing receipt. The name of the first named application is misspelled. It currently appears on the Filing Receipt as "Robert LaPage," but should properly be "Robert LePage." Further, Mr. LePage's Canadian province of "Quebec" is misspelled as "Quebac." Similarly, the second named inventor (Michel Paradis) is also a resident of Quebec, although it is misspelled "Quebac" on the Filing Receipt. It is respectfully requested that these clerical errors, as well as the filing date be corrected on a corrected Filing Receipt. As requested on the filing receipt, a copy of the Filing Receipt with the changes noted thereon is attached hereto as Exhibit C. The Office of Petitions is respectfully requested to forward this request for a corrected Filing Receipt to the Application Processing Division's Customer Correction Branch upon deciding the petition to accord the application the filing date requested by the applicants of December 3, 1998.

If a decision on this petition could be expedited or assisted by a telephone conversation with the undersigned attorney, please contact me at 414-362-0610.

Respectfully submitted,

RITE-HITE HOLDING CORPORATION



Matthew C. McNeill, Reg. No. 35,281
Intellectual Property Counsel
8900 North Arbon Drive
P. O. Box 23043
Milwaukee, WI 53223-0043
(414) 362-0610

A

This Page Blank (uspto)



POST OFFICE TO ADDRESSEE E1847855273US

ORIGIN (POSTAL USE ONLY)

Postage Code	Postage Amount	Postage Paid
000	0.00	0.00
Date in origin	Postage Code	Postage Paid
10/13/95	000	0.00
Time in	Postage Code	Postage Paid
10:30 AM	000	0.00
Weight	Postage Code	Postage Paid
5.14.0	000	0.00
No Delivery	Postage Code	Postage Paid
0	000	0.00

CUSTOMER USE ONLY

Method of Payment	Postage Code	Postage Paid
000	000	0.00
Express Mail	Postage Code	Postage Paid
000	000	0.00

Postage Code	Postage Paid
000	0.00

FROM: Please Print
Matthew C. McNeill
Rite-Site Holding Corporation
2000 N. Arbon Drive
Albuquerque, NM 87102

TO: Please Print
Matthew C. McNeill
Rite-Site Holding Corporation
2000 N. Arbon Drive
Albuquerque, NM 87102

Box 1000
Albuquerque, NM 87102

FOR PICKUP OR TRACKING CALL 1-800-222-1811

Label 11-B October 1995



Customer Copy
SERVICE GUARANTEE AND
INSURANCE COVERAGE LIMITS
SEE REVERSE SIDE FOR
DETAILS

B

This Page blank (uspto)

The Patent Office is respectfully requested to place its stamp on this

POSTAL CARD
and place it in the outgoing mail

The following paper has been received

In re Application of LePage, et al.
Case No. 97-060A; Serial No. 5,579,820
For: Roll-Up Door for Vehicle Shelters
Reissue Application Fee Transmittal Form (in duplicate)
Reissue Application (7 pages Specification/cut-up copy of issued
Specification; 5 pages of 27 claims, 1 page ABSTRACT, 5 pages
drawings from issued Patent); Reissue Patent Application
Transmittal; Reissue Application Declaration by the Inventor (7
pages); 2 "Offer to Surrender Original Patent" (each signed by 1
inventor); Information Disclosure Statement, PTO-1449 and
Copies of IDS Citations (44 references); Request for Abstract of
Title (in duplicate); Return Receipt Postcard
Fee paid by charge to Deposit Account 18-1450
All mailed Under Certificate of Mailing by Express Mail dated
December 3, 1998 - Express Mail No. EI847855273US

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"Express Mail" mailing label number: EI847855273US

Date of Deposit: December 3, 1998


REISSUE APPLICATION

I hereby certify that the documents listed below are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to Box REISSUE APPLICATION, Assistant Commissioner of Patents, Washington, DC 20231:

Reissue Application Fee Transmittal Form (in duplicate)
Reissue Application (7 pages Specification/cut-up copy of issued Specification
5 pages of 27 claims, 1 page ABSTRACT, 5 pages drawings from issued Patent)
Reissue Patent Application Transmittal
Reissue Application Declaration by the Inventor (7 pages)
2 "Offer to Surrender Original Patent" (each signed by 1 inventor)
Information Disclosure Statement, PTO-1449 and
Copies of IDS Citations (44 references)
Request for Abstract of Title (in duplicate)
Return Receipt Postcard

Matthew C. McNeill

Typed name of person mailing paper or fee



Signature of person mailing paper or fee


Applicant(s) LePage, R., et al.

Title Roll-Up Door for Vehicle Shelters

Patent No. 5,579,820 **Filed:** _____

Rite-Hite Holding Corporation
8900 North Arbon Drive
P. O. Box 23043
Milwaukee, WI 53223-0043

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

REISSUE APPLICATION FEE TRANSMITTAL FORM						Docket Number (Optional) 97-060A		
Claims as Filed - Part 1								
Claims in Patent	For	Number Filed in Reissue Application	(3) Number Extra	Small Entity		Other than a Small Entity		
				Rate	Fee	Rate	Fee	
(A) 19	Total Claims (37 CFR 1.16(j))	(B) 27	**** 8 =	x \$	=	or	x \$ 18 = 144	
(C) 1	Independent Claims (37 CFR 1.16(i))	(D) 3	* 2 =	x \$	=		x \$ 78 = 156	
Basic Fee (37 CFR 1.16(h))					\$		\$ 760	
Total Filing Fee					\$	OR	\$ 1,060	
Claims as Amended - Part 2								
	(1) Claims Remaining After Amendment		(2) Highest Number Previously Paid For	(3) Extra Claims Present	Small Entity		Other than a Small Entity	
					Rate	Fee	Rate	Fee
Total Claims (37 CFR 1.16(j))	***	MINUS	**	=	x \$	=	or	x \$ =
Independent Claims (37 CFR 1.16(i))	***	MINUS	*****	=	x \$	=		x \$ =
Total Additional Fee					\$	OR	\$	
<p>* If the entry in (D) is less than the entry in (C), Write "0" in column 3.</p> <p>** If the "Highest Number of Total Claims Previously Paid For" is less than 20, Write "20" in this space.</p> <p>*** After any cancellation of claims</p> <p>**** If "A" is greater than 20, use (B - A); if "A" is 20 or less, use (B - 20).</p> <p>***** "Highest Number of Independent Claims Previously Paid For" or Number of Independent Claims in Patent (C).</p>								
<p><input checked="" type="checkbox"/> Please charge Deposit Account No. <u>18-1450</u> in the amount of <u>1,060</u>. A duplicate copy of this sheet is enclosed.</p> <p><input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees under 37 CFR 1.16 or 1.17 which may be required, or credit any overpayment to Deposit Account No. <u>18-1450</u>. A duplicate copy of this sheet is enclosed.</p> <p><input type="checkbox"/> A check in the amount of \$ _____ to cover the filing / additional fee is enclosed.</p>								
<u>12.03.98</u> Date		 _____ Signature of Applicant, Attorney or Agent of Record						
		<u>Matthew C. McNeill</u> _____ Typed or printed name						

REISSUE APPLICATION FEE TRANSMITTAL FORM

Docket Number (Optional)

97-060A

Claims as Filed - Part 1

Claims in Patent	For	Number Filed in Reissue Application	(3) Number Extra	Small Entity		Other than a Small Entity	
				Rate	Fee	Rate	Fee
(A) 19	Total Claims (37 CFR 1.16(j))	(B) 27	**** 8 =	x \$	=	or	x \$ 18 = 144
(C) 1	Independent Claims (37 CFR 1.16(i))	(D) 3	* 2 =	x \$	=		x \$ 78 = 156
Basic Fee (37 CFR 1.16(h))							\$
Total Filing Fee						\$	OR \$ 1,060

Claims as Amended - Part 2

	(1) Claims Remaining After Amendment		(2) Highest Number Previously Paid For	(3) Extra Claims Present	Small Entity		Other than a Small Entity	
					Rate	Fee	Rate	Fee
Total Claims (37 CFR 1.16(j))	***	MINUS	**	=	x \$	=	or	x \$ =
Independent Claims (37 CFR 1.16(i))	***	MINUS	*****	=	x \$	=		x \$ =
Total Additional Fee						\$	OR	\$

* If the entry in (D) is less than the entry in (C), Write "0" in column 3.

** If the "Highest Number of Total Claims Previously Paid For" is less than 20, Write "20" in this space.

*** After any cancellation of claims

**** If "A" is greater than 20, use (B - A); if "A" is 20 or less, use (B - 20).

***** "Highest Number of Independent Claims Previously Paid For" or Number of Independent Claims in Patent (C).

☒ Please charge Deposit Account No. 18-1450 in the amount of 1,060.
A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any additional fees under 37 CFR 1.16 or 1.17 which may be required, or credit any overpayment to Deposit Account No. 18-1450.
A duplicate copy of this sheet is enclosed.

☐ A check in the amount of \$ _____ to cover the filing / additional fee is enclosed.

12.03.98

Date



Signature of Applicant, Attorney or Agent of Record

Matthew C. McNeill

Typed or printed name

ROLL-UP DOOR FOR VEHICLE SHELTERS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to collapsible vehicle shelters such as those having a structure made of assembled tubular members and cross-members and a complementary covering therefor made of a flexible plastic material and, more particularly, to a roll-up door for the door opening defined at the front of such vehicle shelters.

2. Description of the Prior Art

The present invention relates to roll-up closures for use in collapsible automobile shelters of the type illustrated in U.S. Pat. No. 4,887,627 issued on Dec. 19, 1989 to Audet. Audet discloses an improved collapsible shelter comprising a structure made up of tubular members and cross-members forming an assembly having side walls diverging from top to bottom and a roof section with the structure being covered by a covering complementary in shape to the assembled structure and made up of a weather proof flexible plastic material. At the front of the shelter, there is defined an opening which, in the Audet patent, is rectangular and is closed by curtain-type flexible plastic sheet doors provided on one or two sides of the opening. The opening is obviously intended for allowing the vehicle to access the shelter.

In other shelters, the front opening extends the whole width of the shelter, that is from side wall to side wall of the assembled structure, thereby having the shape of an isosceles trapezoid. Such openings are practical as they are as large as the shelter itself. However, it is difficult to adapt any closure to such a trapezoid-shaped opening and, to this date, roll-up curtain-type flexible closures have been used therefor with these closures being manually rolled-up from one side of the assembled structure laterally towards the other side thereof, whereat they are retained by strings.

Also known is a rectangular closure made of the same flexible material as the vehicle shelter itself which by way of cables and pulleys can be manually raised, in a way more or less similar to horizontal Venetian blinds, towards its retracted position. A number of spaced apart horizontally extending elongated rigid members are fixed to the closure so that the closure includes three sections which fold substantially like conventional garage doors. The sides of the closure are guided in a pair of parallel vertical rigid frame members.

U.S. Pat. No. 4,495,736 issued on Jan. 29, 1985 to Lamontagne discloses a vehicle shelter intended to house the front engine compartment of the automobile. This shelter includes a flexible canvas which surrounds the engine compartment substantially up to the windshield of the vehicle. Warm air is blown under the engine compartment so as to warm not only the crank-case but also the battery and other parts situated therein. The shelter is provided with a vertically rolled-up conventional and rudimentary closure. U.S. Pat. No. 4,150,682 issued on Apr. 24, 1979 to Rycer discloses a vehicle shelter comprising a closet-type enclosure with doors which contains a plurality of arched hoops having ground engaging skids and with a flexible covering being attached to these arched hoops. In storage, the hoops and the covering are retracted into the enclosure. The hoops may be pulled out manually from the enclosure and over a car parked in front thereof. The shelter itself does not actually include any flexible door for access thereto, when expanded.

U.S. Pat. No. 5,123,474 issued on Jun. 23, 1992 to Smith discloses a roll-up closure device made of a flexible material

which is rolled-up on a motor driven tubular cylindrical drum journaled at the ends thereof on bearings. The closure is guided in vertical tracks which define therebetween a rectangular opening with the closure being of rectangular complementary shape.

U.S. Pat. No. 5,042,556 issued on Aug. 27, 1991 to Ruiter discloses a door assembly for a rectangular doorway opening, such as a garage opening, which comprises a flexible door panel which is guided around rotatable guide wheels between a vertical closed position and a horizontal open position.

U.S. Pat. No. 3,878,879 issued on Apr. 22, 1975 to Manns discloses a roll-up door having a flexible door-leaf arranged to be wound about a roller for closing and opening the rectangular door with trolleys running in guide rails being located at the vertical side frames for maintaining the door-leaf in a laterally stretch condition, and with a movable pulley loaded by a weight being provided for maintaining the door-leaf in a vertically stretched position.

U.S. Pat. No. 5,163,495 issued on Nov. 17, 1992 to Lichy discloses a closure assembly for closing a rectangular opening which comprises a pair of vertical guides and a closure member engaged in the guides so that the closure member can slide along the guides. The closure member includes a pair of vertical tape-shaped tracking members disposed on opposite edges thereof and which are retained within the guides. A biasing assembly which enhances lateral tension on the closure member is also suggested.

U.S. Pat. No. 3,749,107 issued on Jul. 31, 1973 to Laberge discloses a collapsible shelter which comprises a plurality of upstanding parallel spaced apart arched members, the lower ends of which being received in a pair of channels fixed to the ground. A flexible covering is spread over the arched members with the lower edges of this covering being held by the channels.

U.S. Pat. No. 3,463,174 issued on Aug. 26, 1969 to Heller discloses a portable cover structure for a vehicle, wherein foldable frame sections have curtain tracks attached thereto, the frame sections being pivotally hinged so as to form, when expanded, a continuous covered level frame defining an uninterrupted curtain track which receives a curtain for completely enclosing the level frame.

U.S. Pat. No. 2,886,104 issued on May 12, 1959 to Swan discloses an awning of rectangular shape which can be displaced between an inoperative retracted position and an operative extended position wherein, when extended, the awning will provide a roof enclosure having its fabric maintained in a taut condition.

U.S. Pat. No. 3,460,602 issued on Aug. 12, 1969 to Hugus discloses a tensioning device for a rectangular flexible roll-up closure, wherein the flexible closure membrane is fastened to a bottom rail which is displaceable relative to an upper roller around which the membrane can be wound and unwound as the closure opens and closes. Tension is applied to the flexible closure membrane by way of a spring and cable system which biases the bottom rail away from the upper roller. The membrane is guided along a pair of vertical trackways.

SUMMARY OF THE INVENTION

It is therefore an aim of the present invention to provide an improved closure device for vehicle shelters.

It is also an aim of the present invention to provide an improved roll-up closure device adapted to close a shelter door opening having a tapered shape and, more particularly,

an isosceles trapezoidal shape, wherein the parallel sides of the trapezoid correspond to the horizontal sides of the door opening, with the door being wound in an horizontal position at the top of the door opening.

It is a further aim of the present invention to provide a roll-up closure device for vehicle shelters which is driven by a reversible motor which can also preferably be actuated from a remote location.

It is a still further aim of the present invention to provide a roll-up closure device for vehicle shelters wherein the flexible closure or door includes laterally inward biasing means for maintaining the flexible closure taut during the opening and closing thereof, and for allowing the flexible closure to somewhat yield depth-wise.

Therefore, in accordance with the present invention, there is provided a roll-up closure device typically for use on vehicle shelters of the type defining at a front end thereof a door opening having lateral sides which diverge from top to bottom, comprising a pair of guide means adapted to be mounted to the vehicle shelter substantially at the lateral sides of the door opening and substantially parallel thereto, an overhead roller means adapted to be rotatably mounted inside the vehicle shelter and substantially horizontally above the door opening, a flexible closure means adapted to be secured at a top end thereof to said roller means, at least a section of said flexible closure having a shape substantially complementary to that of the door opening and including diverging lateral side edges adapted to be engaged in said guide means, whereby a rotation of said roller means causes said flexible closure to displace along said guide means and to wind around said roller means or to unwind therefrom for displacing said flexible closure towards an open or a closed position thereof, respectively.

BRIEF DESCRIPTION OF THE DRAWINGS

Having thus generally described the nature of the invention, reference will now be made to the accompanying drawings, showing by way of illustration a preferred embodiment thereof, and in which:

FIG. 1 is a perspective view of a collapsible shelter for vehicles adapted with a roll-up closure device in accordance with the present invention, the closure device being shown in a closed position thereof;

FIG. 2 is a front elevational view of part of the closure device of FIG. 1 and, more particularly, of a flexible closure thereof and the cables running therethrough;

FIG. 3 is a partly broken way front elevational view of the left hand part of the shelter and the roll-up closure device of FIG. 1;

FIG. 4 is a cross-sectional side elevational view taken along line 4—4 of FIG. 3;

FIG. 5 is a cross-sectional view taken along line 5—5 of FIG. 3;

FIG. 6 is a cross-sectional view taken along line 6—6 of FIG. 3;

FIG. 7 is a cross-sectional view taken along line 7—7 of FIG. 4;

FIG. 8 is a cross-sectional view taken along line 8—8 of FIG. 4;

FIG. 9 is a perspective view of part of the roll-up closure device of the present invention;

FIG. 10 is a longitudinal vertical cross-sectional view of part of the roll-up closure device;

FIG. 11 is a vertical cross-sectional side view of part of the roll-up closure device;

FIG. 12 is a perspective view of a detail of the variant of FIG. 11; and

FIG. 13 is a perspective view of the vehicle shelter and of the roll-up closure device of the present invention, similar to FIG. 1, but showing the roll-up closure device in a half open position and adapted with the variant of FIGS. 11 and 12.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 illustrates a conventional vehicle shelter S adapted with a closure device D in accordance with the present invention, wherein the vehicle shelter S comprises a supporting structure made up of a series of vertically and transversely oriented, spaced apart and parallel, arched members 10 which are connected one to the other by longitudinal cross-members 12 (see FIG. 13), with a covering C being installed around the structure and being attached to the various arched members 10 and cross-members 12. The covering C which is made of a flexible plastic sheet material comprises a roof section 14 wrapped around the arched members 10, and a vertical front section 16 located above the door opening defined in the shelter S for providing access for a vehicle to the inside of the shelter S. The closure device D of the present invention is intended to selectively open or close the door opening of the shelter S. As best seen in FIGS. 1 and 12, the shelter door opening has the shape of an isosceles trapezoid. The closure device D of the present invention is of the roll-up-type and includes a pair of support plate 18 adapted to be fixedly mounted to the structure of the shelter S and, as best seen in FIG. 3, to an upper cross-member 12 thereof by way of a bolt and wing nut assembly 20 of the type already provided in the conventional shelter S for securing the cross-members 12 to the arched members 10. A guide rail 22 is secured to each one of the support plates 18 and extends therefrom in a downwardly and slightly inclined way in such a way as to follow the sides of the trapezoidal door opening. The lower end of each guide rail 22 is secured to a respective lower one of the cross-members 12 again using the bolt and wing nut assembly 20. As seen in FIG. 4, brackets 24 are provided on the support plates 18 and on the guide rails 22 for use with the bolt and wing nut assemblies 20 to secure the closure device D to the shelter S.

Each support plate 18 is provided with a pulley system and a cable system which will be described in details hereinafter. Only one of the support plates 18 and, more particularly, the left one in the drawings is provided with a motor 26 coupled to a reducer gearbox 28 which drives by way of a toothed belt 30 a shaft 32 which extends transversely above the door opening and which is journaled at its ends to the support plates 18. Besides from the motor 26, the reducer gearbox 28 and the toothed belt 30, the equipment provided on each of the support plates 18 is identical.

A flexible closure 34 made of a plastic sheet material which is well illustrated in FIG. 2 is adapted to engage at the sides thereof the guide rails 22 for displacement therealong so that the closure 34 is either wound around the shaft 32 or is unwound therefrom depending on the rotation of the motor 26. As best seen in FIGS. 2 and 5, the closure 34 defines a loop at each side thereof with a cable 36 extending through this loop. As seen in FIG. 2, the closure 34 includes an upper straight section intended to extend above the door opening and to be attached to the shaft 32 and a lower flared

section adapted to follow the shape of the door opening so that, when the closure 34 is closed as in FIG. 1, the closure 34 completely closes off the trapezoidal door opening defined at the front end of the shelter S. A Teflon™ block 38 is fixedly secured near the bottom end of each side of the closure 34 for reasons which will be explained in details hereinafter.

The side edges of the closure 34 and, more particularly, the loops thereof enclosing the cables 36 and the lower blocks 38 enclosing both the closure loops and the cables 36 are received into the guide rails 22 which each define an inwardly facing longitudinal slot 40 for allowing the closure 34 to extend through the guide rails 22, inwardly from the cables 36. As seen in FIG. 4, there is rotatably mounted a lower pulley 42 at the bottom ends of each guide rail 22.

As best seen in FIGS. 2, 4 and 13, each support plate 18 comprises a pulley system which includes a front guide pulley 44 and a double pulley 46 which comprises a slightly outwardly angled outer pulley 48 and a frusto-conical inner pulley 50. The cable 36 is fixedly attached at both ends thereof to the double pulley 46 and, more particularly, one end of the cable 36 is attached to the outer pulley 48 with the other end thereof being attached to the inner pulley 50. From the inner pulley 50, the cable 36 passes around the guide pulley 44 and then runs along the lateral edge of the closure 34 while, as mentioned hereinabove, being secured thereto. At the bottom of the closure 34, the cable 36 extends through the Teflon™ block 38 which is mounted to the lower end of the closure 34. The cable 36 then engages the lower pulley 42 rotatably mounted at the lower end of the guide rail 22. Afterwards, the cable 36 extends upwards, behind the closure 34 and is then secured to the outer pulley 48. Between the lower pulley 42 and the outer pulley 48, at least part of the cable 36 includes an elastic section 54 which acts as a binder for reasons which will be explained hereinafter.

A retaining arm 56 is mounted slightly above the guide pulley 44 for ensuring the engagement of the cable 36 with the guide pulley 44, as best seen in FIG. 4.

As seen in FIGS. 1 and 2, the lower end of the closure 34 comprises a pair of horizontal elastic members 58 which ensure that the closure 34 remains relatively taut at the point of entry thereof in the guide rails 22 when the closure 34 is displaced upwards and gradually becomes "too big" in view of the converging side guide rails 22. Indeed, as the closure 34 gradually moves upwards, the elastic members 58 pick up the slack produced in the closure 34. The teflon™ blocks 38 are located opposite the elastic members 58 in order to ensure that, even with the elastic force applied inwardly by the elastic members 58, the closure 34 and the cables 36 connected thereto can slide along the guide rails 22.

As seen in FIGS. 11 and 12, a variant 38a of the teflon™ block 38 defines an inner lower recess 60 which communicates with a vertical opening 61 for allowing the cable 36 to leave the closure 34 higher than a lower edge 52 thereof. This configuration allows for the lower pulleys 42 to be mounted above the ground surface (as seen in FIG. 13) thereby reducing the possibility that they become jammed because of ice built-ups on or near the ground. Opposite the recess 60, the closure 34 is thus not directly driven by the cable 36, but the rigidity of the block 38a ensures that the lower end 52 of the closure 34 located opposite the recesses 60 of the teflon™ blocks 38a extends firmly downwardly right up to the ground so that the closure 34 properly closes the door opening of the shelter S along the whole height thereof and, more particularly, at the lower end 52 of the closure 34 as it is not driven by the cables 36. Therefore, the

configuration of the teflon™ blocks 38a allow for the lower pulleys 42 to be mounted considerably above the ground to prevent the same from jamming due to ice built-ups, while ensuring that the closure 34 extends vertically and firmly downwards right up to the ground.

As seen in FIGS. 5 and 6, the guide rails 22 are provided with seals 62 inwardly of the slots 40 thereof.

As seen in FIGS. 8 and 10, the overhead shaft 32 does not extend through the double pulleys 46, but rather includes an extension 64 of small diameter which extends outwardly therefrom and through the double pulley 46. The shaft extension 64 then extends outwardly through bearings 66 secured to the support plate 18 and, outwardly of the support plate 18, the shaft extension 64 is fixedly received in a square-toothed gear 68 (e.g. a timing gear), the teeth of the toothed belt 30 being engaged between the teeth of the timing gear 68 for drivingly connecting the motor 26 and reducer gearbox 28 to this timing gear 68.

With reference to FIGS. 3, 4 and 8, it is understood that, when the closure 34 is closed, an appropriate rotation of the motor 26 causes a rotation of the shaft 32 along arrow 70 of FIG. 3 thereby causing the cables 36 to displace along arrow 72 of FIG. 4, whereby the cables 36 gradually wind around the inner pulleys 50 while the closure 34 is being raised along the guide rails 22 along arrow 74 of FIG. 3 and arrow 76 of FIG. 13, the lateral edges of the closure 34 which enclose the cables 36 gradually winding around the inner pulleys 50 (see FIG. 10) while the cables 36 simultaneously unwind from the outer pulleys 48 along arrow 78 of FIG. 4. As the closure 34 is being raised, the effective width thereof increases but, in view of the tapered configuration of the inner pulleys 50 (again see FIG. 10), the closure 34 will wind around the shaft 32 while remaining substantially taut in view of the outward stacking of the cables 36 onto the inner pulleys 50. The outer pulleys 48 are slightly angled to facilitate the unwinding and winding of the cables 36 therearound in view of the angular orientation of the cables 36 below the outer pulleys 48, as seen in FIG. 8. Furthermore, the tapered configuration of the inner pulleys 50 ensures that the closure 34 winds there around in an orderly fashion, as seen in FIG. 10. As seen in FIG. 3, the cable 36 is directed by the guide pulley 44 towards the larger outward end of the tapering inner pulley 50 so that the cable 36 can then appropriately slide downwards and inwards from this outward end of the inner pulley 50 towards the inward smaller end thereof, thereby ensuring a neat and orderly stacking of the coils of the cable 36 around the inner pulley 50.

The elastic portion 54 of each cable 36 acts as a binder to ensure that the cables 36 remain taut during the operation of the closure 34 in view of the fact that, during rotation of the double pulleys 46, the amount of cable which is being wound around one of the outer and inner pulleys 48 and 50 thereof is normally different from the amount of cable which unreels from the other one of the outer and inner pulleys 48 and 50, respectively.

Even though there are elastic portions 54 in the mechanism for driving the closure 34 between the open and closed positions thereof, the motor 26 acts directly on the closure 34 during the ascension thereof, i.e. its displacement towards its open position, as it is the unextendable cables 36 which act on the closure 34, the binder mechanism provided by the elastic portions 54 being only functional during the lowering of the closure 34. This configuration allows the motor 26 to exert direct forces on the closure when it is being opened thereby enabling the motor 26 to dislodge the lower

end of the closure 34, for instance, from ice having built up thereat while the closure 34 was closed.

Alternatively, the elastic portions 54 can be replaced by springs 84, as seen in FIG. 11, which might have a more constant spring force for the various operating temperatures of the closure device D.

The elastic members 58 again will ensure that the slack gradually provided in the closure 34 when it is raised is taken up substantially centrally of the closure 34 and not at the lateral edges thereof in order to ensure a proper sliding action of the closure 34 along the guide rails 22, that is to prevent a jamming of the lateral edges of the closure 34 in the slots 40 of the guide rails 22.

A reverse operation of the motor 26 causes the cables 36 to wind around the outer pulleys 48 of the double pulleys 46, whereby the closure 34 is pulled downwards along the guide rails 22 and thus unwinds gradually from the inner tapered pulleys 50 of the double pulleys 46.

As well known in the art of garage doors, a remote control can be provided for remotely operating the motor 26 thereby allowing the user to open and close the closer 34 at a distance and, for instance, from within a vehicle.

When the closure 34 is closed, the elastic members 58 can still be somewhat extended in order to allow for the closure 34 to sufficiently yield when a force is applied thereon, such as by snow being thrown thereon by a snowplow or the like, thereby preventing rupture of the closure 34.

As seen in FIG. 8, the ends of the cables 36 are secured to the outer pulleys 48 by screws 80 and to the inner pulleys 50 by screws 82.

For manual opening and closing of the closure 34 in case of a failure of the motor 26 or in case of the closure 34 becoming jammed in the guide rails 22 due to ice, there are provided a pair of side zippers 86 (see FIGS. 1 and 2) which extend parallel to and slightly inwards of the guide rails 22, whereby the closure can be manually rolled and then attached at the top of the door opening with strings 88.

Accordingly, by way of the closure device D of the present invention, a flared door opening defined in a vehicle shelter C can be completely closed in a substantially taut way and, when the closure is being raised or generally when it is at least partly wound around the overhead shaft, the closure is wound in an orderly and taut fashion around this overhead shaft. The closure device of the present invention thus allows for a motorized closure to be installed on a vehicle shelter without reducing the effective width of the door opening thereof.

We claim:

1. A roll-up closure device typically for use on vehicle shelters of the type defining at a front end thereof a door opening having lateral sides which diverge from top to bottom, comprising a pair of guide means adapted to be mounted to the vehicle shelter substantially at the lateral sides of the door opening and substantially parallel thereto thereby diverging from top to bottom an overhead roller means adapted to be rotatably mounted inside the vehicle shelter and substantially horizontally adjacent an upper end of the door opening, a flexible closure means adapted to be secured at a top end thereof to said roller means, at least a section of said flexible closure means having a shape which tapes in direction of said roller means and including diverging lateral side edges adapted to be engaged in said guide means, whereby a rotation of said roller means causes said flexible closure means to displace along said guide means and to wind around said roller means or to unwind therefrom for displacing said flexible closure means towards an open or a closed position thereof, respectively, wherein in said closed position, said section of said flexible closure means substantially completely closes the door opening.
2. A closure device as defined in claim 1, wherein said roller means comprise winding means adapted to take up substantially triangular lateral end portions of said section such that when said flexible close means is in a rolled attitude around said roller means, said flexible closure means defines substantially concentric and cylindrical layers of varying axial width.
3. A close device as defined in claim 2, wherein said roller means comprise a rotatable shaft with said top end of said flexible closure means being attached thereto, a pair of pulley means mounted at ends of said shaft, cable means being engaged to said pulley means and secured to said flexible closure means such that a rotation of said shaft and pulley means cause said cable means to displace thereby displacing said flexible closure means.
4. A closure device as defined in claim 3, wherein each said pulley means comprise first pulley having an outwardly flaring bottom for receiving said lateral side edicts of said flexible closure means in an axially outwardly staggered relationship therearound for maintaining substantially taut said cylindrical layers of said section in said rolled attitude.

5. A closure device as defined in claim 4, wherein said cable means are connected to said pulley means such as to define closed loops, each said pulley means comprising a second pulley adjacent said first pulley, each said cable means being secured to both said first and second pulley such that a rotation of said pulley means causes said cable means to wind around one of said first and second pulleys and to unwind from another one of said first and second pulleys.

6. A closure device as defined in claim 4, wherein said first pulley is frusto-conical shaped.

7. A closure device as defined in claim 5, wherein a third pulley engaged by said cable means is provided at a lower end of each said guide means, whereby when said flexible closure means is displaced towards said closed position thereof, said flexible closure means and said cable means attached thereto unwind from said first pulleys with said cable means being also wound around said second pulleys while driving said flexible closure means downwardly along said guide means such as to substantially completely close the door opening; whereas when said flexible closure means is displaced towards said open position thereof, said flexible closure means and said cable means attached thereto wind around said first pulleys while upwardly pulling said flexible closure means along said guide means with said cable means being also unwound from said second pulleys.

8. A closure device as defined in claim 5, wherein said second pulleys are slightly angled outwardly towards said guide means for cleanly receiving said cable means therein during rotation of said roller means towards said closed position.

9. A closure device as defined in claim 5, wherein said cable means are each provided with binding means to ensure sufficient tension therein during rotation of said roller means.

10. A closure device as defined in claim 1, wherein said flexible closure means is provided with elastic means extending substantially laterally at least adjacent said side edges to ensure that said flexible closure means remains substantially taut during rotation of said roller means.

11. A closure device as defined in claim 10, wherein said guide means each comprise a tubular member adapted to be mounted to the lateral sides defining the door opening of the vehicle shelter and inwardly defining a longitudinal slot, said lateral side edges of said flexible closure means being engaged in said tubular members and inwardly extending therefrom through said slots, said elastic means maintaining said side edges substantially taut at said slots.

12. A closure device as defined in claim 11, wherein each said guide means comprise sealing means mounted to said tubular member at said slot and at least on one side of said lateral side edges of said flexible closure means.

13. A closure device as defined in claim 1, wherein reversible motor means are provided for driving said roller means.

14. A closure device as defined in claim 1, wherein first detachable fastening means are provided on said flexible closure means inwardly of each said lateral side edge thereof for allowing said flexible closure means to be manually opened in the event that said roller means cannot be rotated or that said flexible closure means is jammed to said guide means.

15. A closure device as defined in claim 14, wherein second detachable fastening means are provided for securing said flexible closure means in an open position when having been manually opened using said first detachable fastening means.

16. A closure device as defined in claim 15, wherein said first detachable fastening means comprise zippers, and wherein said second detachable fastening means comprise strap means.

17. A closure device as defined in claim 1, wherein said flexible closure means extends substantially planarly across the door opening when in said closed position.

18. A closure device as defined in claim 11, wherein said lateral side edges of said flexible closure means are each secured opposite said elastic means to a sliding block means engaged in

said tubular member for ensuring that said flexible closure means can displace along said guide means even with forces applied inwardly on said lateral side edges by said elastic members.

19. A closure device as defined in claim 18, wherein each said sliding block means comprises a pulley engaged by said cable means and mounted at a distance a lower end of said lateral side edge of said flexible closure means being mounted to said lower end of said sliding block means, said lower end of said sliding block means being adapted to extend in said guide means at least close to the ground in said closed position such that a lower edge of said flexible closure means extends at least close to the ground whereby said pulley, being mounted fairly above the ground, and said cable means are not as vulnerable to jamming due to ice built-ups with said sliding block means ensuring that said flexible closure means extends firmly downwards to the ground.

20. A roll-up closure device disposed adjacent a door opening and movable between blocking and unblocking position relative thereto, and comprising:

a roller adapted to be rotatably mountable adjacent an upper end of the door opening;

a curtain adapted to be secured at a top end thereof to the roller whereby rotation of the roller causes the curtain to wind or unwind from the roller to move between unblocking and blocking positions, respectively;

guide members disposed at the lateral sides of the door opening;

guide engagement members couplable to the curtain for movement therewith and engageable with the guide members to restrict their movement toward the curtain center; and

a discrete elastic member coupled to the curtain for movement therewith and extending laterally across the curtain, and disposed such that the elastic member can be stretched between the restricted guide engagement members.

21. The device of claim 20, wherein opposed ends of the elastic member are coupled to the curtain, and the restricted guide engagement members are coupled to the lateral edges of the curtain, an increased lateral separation of the guide engagement members exerting a pulling force on the curtain tending to stretch the elastic member.

22. The device of claim 20, wherein the elastic member can be stretched to allow the curtain to yield to an applied external force without rupturing.

23. The device of claim 20, wherein the guide engagement members are cables extending along the lateral edge of the curtain and received in a pocket formed therein.

24. The device of claim 20, wherein the guide engagement members are blocks coupled to the lateral edges of the curtain at approximately the same height as the elastic member.

25. The device of claim 20, and including a second elastic member coupled to the curtain for movement therewith and extending laterally across the curtain such that the second elastic member can be stretched between the restricted guide engagement members.

26. A roll-up closure device disposed adjacent a door opening and movable between blocking and unblocking position relative thereto, and comprising:

a roller adapted to be rotatably mountable adjacent an upper end of the door opening;

a curtain adapted to be secured at a top end thereof to the roller whereby rotation of the roller causes the curtain to wind or unwind from the roller to move between unblocking and blocking positions, respectively;

guide members disposed at the lateral sides of the door opening; and

laterally inwardly biasing means for maintaining the curtain taut, and for allowing the curtain to yield depth-wise for an applied force.

27. The device of claim 26, wherein the laterally inward biasing means comprises:

guide engagement members couplable to lateral edges of the curtain for movement therewith and engageable with the guide members to restrict their movement toward the curtain center; and



a discrete elastic member coupled to the curtain for movement therewith and extending laterally across the curtain, and disposed such that the elastic member can be stretched between the restricted guide engagement members.





[57]




ABSTRACT



A roll-up closure device for typically collapsible vehicle shelters of the type having a structure made of assembled tubular members and cross-members and a complementary covering therefor made of a flexible plastics material and defining at the front end thereof a door opening. The side walls of the shelter are inclined in such a way as to diverge from top to bottom, whereby the door opening has generally a isosceles trapezoidal shape. The device includes a pair of opposed side guide rails mounted at laterally opposite sides of the door opening so as to follow the angled sides thereof, an overhead motor driven roll-up boom extending above the door opening, and a flexible closure shaped like the door opening and having its lateral side edges slidably engaged in the guide rails, whereby the closure device does not substantially reduce the lateral dimensions of the door opening. Cables attached to the roll-up boom are secured to the lateral edges of the closure so that the rotation of the boom causes the cables to wind around respective tapered pulleys provided near each end of the boom with the closure in a rolled attitude extending between the pulleys. Stretched elastics are secured to the lower part of the closure to laterally retract the side edges of the latter towards each other as the closure is being raised. A tensioning mechanism is provided to ensure that the cables remain taut at any position of the closure.



19 Claims, 5 Drawing Sheets











Please type a plus sign (+) inside this box → ☐

PTO/SB/50 (4/98)

Approved for use through 09/30/2000. OMB 0651-0033

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

REISSUE PATENT APPLICATION TRANSMITTAL

Address to: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231	Attorney Docket No.	97-060A
	First Named Inventor	LePage, R.
	Original Patent Number	5,579,820
	Original Patent Issue Date (Month/Day/Year)	12/03/96
	Express Mail Label No.	E1847855273US

APPLICATION FOR REISSUE OF: ☒ **Utility Patent** ☐ **Design Patent** ☐ **Plant Patent**
(check applicable box)

APPLICATION ELEMENTS	ACCOMPANYING APPLICATION PARTS
1. <input checked="" type="checkbox"/> * Fee Transmittal Form (PTO/SB/56) (Submit an original, and a duplicate for fee processing)	7. <input type="checkbox"/> Foreign Priority Claim (35 U.S.C. 119) (if applicable)
2. <input checked="" type="checkbox"/> Specification and Claims (amended, if appropriate)	8. <input checked="" type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input checked="" type="checkbox"/> Copies of IDS Citations
3. <input checked="" type="checkbox"/> Drawing(s) (proposed amendments, if appropriate)	9. <input type="checkbox"/> English Translation of Reissue Oath/Declaration (if applicable)
4. <input checked="" type="checkbox"/> Reissue Oath / Declaration (original or copy) (37 C.F.R. § 1.175)(PTO/SB/51 or 52)	10. <input type="checkbox"/> Statement(s) <input type="checkbox"/> Statement filed in prior application, * Small Entity Status still proper and desired (PTO/SB/09-12)
5. Original U.S. Patent <input checked="" type="checkbox"/> Offer to Surrender Original Patent (37 C.F.R. § 1.178) (PTO/SB/53 or PTO/SB/54) or <input type="checkbox"/> Ribboned Original Patent Grant <input type="checkbox"/> Affidavit / Declaration of Loss (PTO/SB/55)	11. <input type="checkbox"/> Preliminary Amendment
6. Original U.S. Patent currently assigned? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No (If Yes, check applicable box(es)) <input type="checkbox"/> Written Consent of all Assignees (PTO/SB/53 or 54) <input type="checkbox"/> 37 C.F.R. § 3.73(b) Statement <input type="checkbox"/> Power of Attorney	12. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
	13. <input checked="" type="checkbox"/> Other: <u>Request for Abstract of Title</u>

* NOTE FOR ITEMS 1 & 10: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

14. CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number or Bar Code Label <input type="checkbox"/> Correspondence address below (Insert Customer No. or Attach bar code label here)					
Name	Matthew C. McNeill Rite-Hite Holding Corporation				
Address	8900 North Arbon Drive P.O. Box 23043				
City	Milwaukee	State	WI	Zip Code	53223
Country	U.S.A.	Telephone	414 362-0610	Fax	414 355-6578

NAME (Print/Type)	Matthew C. McNeill	Registration No. (Attorney/Agent)	35,281
Signature		Date	12.03.98

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.
 Approved for use through 8/30/00. OMB 0581-0033
 Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

REISSUE APPLICATION DECLARATION BY THE INVENTOR

Docket Number (Optional)

97-060A

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is described and claimed in patent number 5,579,820, granted December 3, 1996, and for which a reissue patent is sought on the invention entitled Roll-Up Door for Vehicle Shelters

the specification of which

☒ is attached hereto.

☐ was filed on _____ as reissue application number _____ / _____
 and was amended on _____
 (if applicable)

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I verily believe the original patent to be wholly or partly inoperative or invalid, for the reasons described below. (Check all boxes that apply.)

☐ by reason of a defective specification or drawing.

☒ by reason of the patentee claiming more or less than he had the right to claim in the patent.

☐ by reason of other errors.

At least one error upon which reissue is based is described as follows:

See attached "Statement of Error under 37 C.F.R. 1.175(a)(3)" (5 pages) incorporated herein by reference.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.5 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Approved for use through 9/30/00. OMB 0451-0033
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

(REISSUE APPLICATION DECLARATION BY THE INVENTOR, page 2)

Docket Number (Optional)
97-060A

All errors corrected in this reissue application arose without any deceptive intention on the part of the applicant. As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Name(s)

Registration Number

Matthew C. McNeill**35,281**

Correspondence Address: Direct all communications about the application to:

☐ Customer Number

OR

Type Customer Number here

Place Customer Number Bar
Code Label here

<input checked="" type="checkbox"/> Firm or Individual Name	Matthew C. McNeill				
Address	Rite-Hite Holding Corporation				
Address	8900 North Arbon Drive				
City	Milwaukee	State	WI	ZIP	53223
Country	U.S.A.				
Telephone	414 362-0610	Fax	414 355-6578		

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine and imprisonment, or both, under 18 U.S.C. 1001, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this declaration is directed.

Full name of sole or first inventor (given name, family name)

Robert LaPage

Inventor's signature

X Robert LaPage

Residence

332 Pierre Cote, Bois-des-Fillon

Date

December 3, 1998

Post Office Address

Quebec, Canada, J6Z 4A2

Citizenship

CANADIAN

Full name of second joint inventor (given name, family name)

Michel Paradis

Inventor's signature

1115 Lac de Mal, Fabreville, Laval

Date

December 3, 1998

Residence

Quebec, Canada, H7P 3M3

Citizenship

CANADIAN

Post Office Address

Full name of third joint inventor (given name, family name)

Inventor's signature

Date

Residence

Citizenship

Post Office Address

☐ Additional joint inventors are named on separately numbered sheets attached hereto.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Reissue Application of:

Patentees: LePage, R. and Paradis, M.

Patent Number: 5,579,820

Granted: December 3, 1996

For: Roll-Up Door for Vehicle Shelters

STATEMENT OF ERROR UNDER 37 C.F.R. §1.175(a)(3)

During preparation and prosecution of the application resulting in the original issuance of the Patent (5,579,820), the primary focus was on a roll-up closure device in the specific environment of a vehicle shelter. As a result, limitations were erroneously included in the claims that were dictated by this environment of use rather than being required for patentability, leading to us (the applicants) claiming less than that to which we were entitled.

Specifically, the preamble of claim 1 (the only independent claim) requires that the roll-up closure device be “typically for use on vehicle shelters of the type defining at a front end thereof” a door opening. The closure device of the invention, however, can be used in conjunction with any doorway or opening, not just one associated with a vehicle shelter. The preamble goes on to state that the door opening has lateral sides “which diverge from top to bottom.” Again, it is our belief that the inventive closure could be used on a doorway or opening that does not have divergent lateral sides.

In re Reissue Application of
LePage, R. and Paradis, M.
for U.S. Patent 5,579,820

Claim 1, in the body thereof, requires that the “guide means” or rails 22 mounted at the lateral sides of the door be disposed so that they are “diverging from top to bottom.” Similarly, claim 1 requires the curtain to include “diverging lateral side edges.” However, this divergence is a byproduct of the fact that our door is disposed on a vehicle shelter comprised of a series of arched members 10 which similarly diverge from top to bottom. To make the opening as large as possible, the closure or door disclosed in the application was sized and shaped to match the divergence of the side edges of the structure, leading in turn to the curtain edges as well as the guide means or rails 22 being similarly divergent. That is, these limitations are tied to the unnecessary limitations identified in the preamble to the claim. However, neither the environmental limitations in the preamble, nor the limitation of divergent curtain edges, nor the limitation of divergent guide means are required in what we believe to be the patentable combination presented in new claim 20 - particularly the combination of a roller, a curtain secured to the roller to wind and unwind therefrom, guide members disposed adjacent the lateral sides of the opening (not necessarily divergent); guide engagement members couplable to the curtain and engageable with the guide members to restrict their movement toward the curtain center, and a discrete elastic member coupled to the curtain and disposed such that the elastic member can be stretched between the restricted guide engagement member. While the stretching of the elastic member may have been enhanced by the fact that the guide means diverged from top to bottom in the disclosed embodiment, there was no need for this limitation in the claim. Rather, non-diverging guide means could be provided at adequate spacing to stretch the elastic

In re Reissue Application of
LePage, R. and Paradis, M.
for U.S. Patent 5,579,820

member between the guide engagement members as restricted by the guide means. Alternatively, the elastic member could be stretched between the restricted guide extension members by an external force applied to the curtain, such that the presence of the elastic member could prevent the curtain from rupturing (new claim 22). Thus, at least the inclusion in the claims of the unnecessary environmental limitations and structural limitations of diverging guide means and curtain edges are sufficient error to support reissuance of this patent. For ease of reference, independent claim 1 is reproduced below, with the erroneously-included environmental and structural limitations shown bracketed and in bold.

1. A roll-up closure device [typically] for [use on vehicle shelters of the type defining at a front end thereof] a door opening having lateral sides [which diverge from top to bottom,] comprising a pair of guide means adapted to be mounted [to the vehicle shelter substantially] at the lateral sides of the door opening [and substantially parallel thereto thereby diverging from top to bottom] an overhead roller means adapted to be rotatably mounted inside the vehicle shelter and substantially horizontally adjacent an upper end of the door opening, a flexible closure means adapted to be secured at a top end thereof to said roller means, [at least a section of said flexible closure means having a shape which tapes in direction of said roller means] and including [diverging] lateral side edges adapted to be engaged in said guide means, whereby a rotation of said roller means causes said flexible closure means to displace along said guide means and to wind around said roller means or to unwind therefrom for displacing said flexible closure means towards an open or a closed position thereof, respectively, wherein in

In re Reissue Application of
LePage, R. and Paradis, M.
for U.S. Patent 5,579,820

said closed position, said section of said flexible closure means
substantially completely closes the door opening.

Moreover, this error occurred without any deceptive intent. As indicated, it arose primarily because of the structure of the vehicle shelter structure on which the closure of the invention was used, leading to an unnecessary focus on that environment in the claims. Indeed, until recently, we had no appreciation that the patent was unduly narrow in this regard. However, on 25 November 98, we were contacted by Rite-Hite Holding Corporation. Rite-Hite expressed their opinion to us that our patent contained an error in that it claimed less than that to which we were entitled. When we realized that the focus in the application on diverging sideframes was unnecessary, we agreed that our claims were perhaps unduly narrow. Having come to that conclusion, we immediately authorized the filing of this reissue request.

This document is incorporated by reference into "Reissue Application Declaration by the Inventor" dated 03 December 98.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Approved for use through 9/30/00. OMB 0861-0033
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

REISSUE APPLICATION BY THE INVENTOR, OFFER TO SURRENDER PATENT		Docket Number (Optional) 97-060A
<p>This is part of the application for a reissue patent based on the original patent identified below.</p>		
Name of Patentee(s) LePage, Robert and Paradis, Michel;		
Patent Number 5,579,820	Date Patent Issued December 3, 1996	
Title of Invention Roll-Up Door for Vehicle Shelters		
<p>I am the inventor of the original patent.</p> <p>I offer to surrender the original patent.</p> <p>1. <input type="checkbox"/> Filed herein is a certificate under 37 CFR 3.73(b).</p> <p>2. <input checked="" type="checkbox"/> Ownership of the patent is in the inventor(s), and no assignment of the patent has been made.</p> <p>One of boxes 1 or 2 above must be checked.</p> <p>The written consent of all assignees owning an undivided interest in the original patent is included in this application for reissue.</p>		
Signature X <i>Robert LePage</i>		Date December 3, 1998
Typed or printed name Robert LePage		
The assignee owning an undivided interest in said original patent is _____ and the assignee consents to the accompanying application for reissue.		
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application, any patent issued thereon, or any patent to which this declaration is directed.		
Name of assignee		
Signature of person signing for assignee		Date
Typed or printed name and title of person signing for assignee		

Burden Hour Statement: This form is estimated to take 0.1 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Approved for use through 8/30/00, OMB 0551-0033
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

PTO/SB/53 (12-87)

REISSUE APPLICATION BY THE INVENTOR, OFFER TO SURRENDER PATENT		Docket Number (Optional) 97-060A
<p>This is part of the application for a reissue patent based on the original patent identified below.</p> <p>Name of Patentee(s) LePage, Robert and Paradis, Michel</p> <p>Patent Number 5,579,820</p> <p>Date Patent issued December 3, 1996</p> <p>Title of Invention Roll-Up Door for Vehicle Shelters</p>		
<p>I am the inventor of the original patent.</p> <p>I offer to surrender the original patent.</p> <p>1. <input type="checkbox"/> Filed herein is a certificate under 37 CFR 3.73(b).</p> <p>2. <input checked="" type="checkbox"/> Ownership of the patent is in the inventor(s), and no assignment of the patent has been made.</p> <p>One of boxes 1 or 2 above must be checked.</p> <p>The written consent of all assignees owning an undivided interest in the original patent is included in this application for reissue.</p>		
<p>Signature <i>X Michel Paradis</i></p>		<p>Date December 3, 1998</p>
<p>Typed or printed name Paradis, Michel</p>		
<p>The assignee owning an undivided interest in said original patent is _____ and the assignee consents to the accompanying application for reissue.</p>		
<p>I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application, any patent issued thereon, or any patent to which this declaration is directed.</p>		
<p>Name of assignee</p>		
<p>Signature of person signing for assignee</p>		<p>Date</p>
<p>Typed or printed name and title of person signing for assignee</p>		

Burden Hour Statement: This form is estimated to take 0.1 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Reissue Application of:

Patentees: LePage, R. and Paradis, M.

Patent Number: 5,579,820

Granted: December 3, 1996

For: Roll-Up Door for Vehicle Shelters

REQUEST FOR ABSTRACT OF TITLE


Assistant Commissioner
for Patents
Washington, D.C. 20231

Dear Sir:

Please prepare a certified Abstract of Title in respect of the above-identified original patent, for placing in the official file of the Reissue Application which is filed herewith.

For the fee required by 37 CFR 1.19(b)(4), please charge Deposit Account 18-1450 in the amount of \$25.00. Charge any additional fees or credit any overpayment to Account No. 18-1450. A duplicate of this request is attached.

Respectfully submitted,



Matthew C. McNeill, Reg. No. 35,281
Intellectual Property Counsel
8900 North Arbon Drive
P. O. Box 23043
Milwaukee, WI 53223-0043
(414) 362-0610

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Reissue Application of:

Patentees: LePage, R. and Paradis, M.

Patent Number: 5,579,820

Granted: December 3, 1996

For: Roll-Up Door for Vehicle Shelters

INFORMATION DISCLOSURE STATEMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Pursuant to 37 C.F.R. §§ 1.97 and 1.98, the references listed on the enclosed PTO-1449 are submitted for consideration by the Examiner in the examination of the above-identified reissue patent application.

The full consideration of the references in their entirety by the Examiner is respectfully requested and encouraged. Also, it is respectfully requested that the references be entered into the record of the present application and that the Examiner place his or her initials in the appropriate area on the enclosed Form PTO-1449, thereby indicating the Examiner's consideration of each of the references.

The submission of the references listed on the Form PTO-1449 is for the purpose of providing a complete record and is not a concession that the references listed thereon are prior art to the invention claimed in the patent application. The right is expressly reserved to establish an invention date earlier than the above-identified filing date in order to remove any reference submitted herewith as prior art should it be deemed appropriate to do so.

Further, the submission of the references is not to be taken as a concession that any reference represents art that is relevant or analogous to the claimed invention. Accordingly, the right to argue that any reference is not properly within the scope of prior art relevant to an examination of the claims in the above-identified application is also expressly reserved.

The Information Disclosure Statement is being filed:

- ☒ (a) within three months of the filing date of the patent application, (b) within three months of the date of entry into the national stage as set forth in 37 C.F.R. § 1.491 of the international applications, or (c) before the mailing date of a first Office Action on the merits.
- ☐ after (a), (b), or (c) above, but before the mailing date of a final action under 37 C.F.R. § 1.113 or a Notice of Allowance under 37 C.F.R. § 1.311, and includes:
 - ☐ the Certification under 37 C.F.R. § 1.97(e) (see "Certification" below).
 - ☐ the fee of \$240 set forth in 37 C.F.R. § 1.17(b) (see "Fees" below).
- ☐ after the mailing date of a final action under 37 C.F.R. § 1.113 or a Notice of Allowance under 37 C.F.R. § 1.311, and includes the Certification under 37 C.F.R. § 1.97(e) (see "Certification" below), a Petition requesting consideration of the Information Disclosure Statement (see "Petition" below), and the Petition Fee set forth in 37 C.F.R. § 1.17(i) (see "Fees" below).

Copies of The References

- ☒ Copies of the references listed on the enclosed Form PTO-1449 are enclosed herewith. Attached to each reference not in the English language is a concise explanation of the relevance pursuant to 37 C.F.R. § 1.98(a)(3), or a translation thereof.
- ☐ A copy of the foreign search report is enclosed herewith.
- ☐ The references listed on the enclosed Form PTO-1449 were previously identified in the parent application(s) of the present application, and copies of the references were furnished at that time. Accordingly, additional copies of the references are not submitted herewith, so as not to burden the file with duplicate copies of references. The Examiner is respectfully requested to carefully review the references in accordance with the requirements set out in the Manual of Patent Examining Procedure. In accordance with 37 C.F.R. § 1.98(d), the details of the parent

application(s) relied upon for an earlier filing date under 35 U.S.C. § 120 in which copies of the references were previously furnished are set out below:

U.S. APPLICATIONS		Status (<i>check one</i>)		
U.S. APPLICATIONS	U.S. FILING DATE	PATENTED	PENDING	ABAN- DONED
1. 0 /				
2. 0 /				
3. 0 /				

Other Pending Applications

- ☐ The Examiner's attention is directed to the following U.S. patent application(s):

U.S. APPLICATIONS		Status (<i>check one</i>)		
U.S. APPLICATIONS	U.S. FILING DATE	PATENTED	PENDING	ABAN- DONED
1. 0 /				
2. 0 /				
3. 0 /				

Certification

- ☐ The **undersigned attorney** hereby certifies that each item of information contained in the Information Disclosure Statement was cited in a communication from a foreign patent office in a counterpart foreign patent application not more than three months prior to the filing of the Information Disclosure Statement.
- ☐ The **undersigned attorney** hereby certifies that no item of information contained in the Information Disclosure Statement was cited in a communication from a foreign patent office in a counterpart foreign patent application or, to the knowledge of the attorney signing after making reasonable inquiry, was known to any individual

In re Reissue application of
R. Lepage and M. Paradis
USP 5,579,820

designated in 37 C.F.R. § 1.56(c) more than three months prior to the filing of the Information Disclosure Statement.

Petition

- ☐ The undersigned attorney hereby petitions the Commissioner to consider this Information Disclosure Statement and the references listed on the enclosed Form PTO-1449 in the examination of the above-identified patent application.

Fees

- ☒ No fee is owed by the applicant(s).
- ☐ The **IDS Fee of \$240.00** under 37 C.F.R. § 1.17(p) is enclosed herewith. (See Method of Payment of Fees below.)
- ☐ The **Petition Fee of \$130.00** set forth in 37 C.F.R. § 1.17(i) is enclosed herewith.

Method Of Payment Of Fees

- ☐ Attached is a check in the amount of \$240.00.
- ☐ Charge Deposit Account No. 18-1450 in the amount of \$240. (A duplicate copy of this communication is enclosed for that purpose.)

In re Reissue application of
R. Lepage and M. Paradis
USP 5,579,820

Authorization To Charge Additional Fees

- ☒ If any additional fees are owed in connection with this communication, please charge
Deposit Account No. 18-1450.
- ☐ Refund.

Dated: December 3, 1998



Matthew C. McNeill, Reg. No. 35,281
Intellectual Property Counsel
RITE-HITE HOLDING CORPORATION
8900 North Arbon Drive
P. O. Box 23043
Milwaukee, WI 53223-0043
(414) 362-0610 (telephone)
(414) 355-6578 (fax)

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Use several sheets if necessary)

APPLICANT
LePage, et al.

FILING DATE

GROUP

U.S. PATENT DOCUMENTS

EXAMINER INITIAL		DOCUMENT NUMBER	DATE	NAME	CLASS	SUBCLASS	FILING DATE IF APPROPRIATE
		1,033,224	07/23/12	R. Andlauer			
		3,878,879	04/22/75	Mannes			
		4,016,920	04/12/75	Shepard			
		4,452,292	03/05/84	Leivenzon et al.			
		4,478,268	10/23/84	Palmer			
		4,569,383	02/11/86	Wentzel			
		4,601,320	04/22/86	Taylor			
		4,800,946	01/31/89	Rosenoy			
		4,884,617	12/05/89	Coenraets			
		4,887,660	12/19/89	Kraus			
		4,896,714	01/30/90	Ellis			
		5,025,847	03/25/95	Mueller			
		5,048,588	09/17/91	Weishar et al.			
		5,056,579	10/15/91	Krafutler			
		5,078,197	01/07/92	Weishar			
		5,123,474	03/23/92	Smith			
		5,139,074	08/92	Warner			
		5,139,075	08/18/92	Desrochers			
		5,141,043	08/92	Krauetler			
		5,141,044	08/25/92	Hying et al.			
		5,207,256	05/04/93	Kraeutler			
		5,222,541	03/29/93	Hornberger			
		5,271,448	12/21/93	Delgado			
		5,299,617	04/05/94	Hying et al.			
		5,353,859	10/11/94	Oltahfer et al.			
		5,477,902	12/95	Kraeutler			
		5,526,865	01/18/96	Coenraets			
		5,535,805	07/96	Kellogg et al			

		5,638,883	06/97	Schulte			


FOREIGN PATENT DOCUMENTS

		DOCUMENT NUMBER	DATE	COUNTRY	CLASS	SUBCLASS	TRANSLATION	
							YES	NO
		240,349	10/01/25	Great Britain				X
		503,774	04/11/39	Great Britain				X
		1,009,862	06/04/52	France			X	
		1,444,017	04/28/72	Great Britain				X
		125,217	11/14/84	EPO				X

OTHER DOCUMENTS (Including Author, Title, Date, Pertinent Pages, Etc.)

			"Re-Coil Away Specifications"; M & I Door Systems Limited; Date unknown; 2 pages.
			"Re-Coil-Away" Door System Installation Instructions"; M & I Door Systems, Ltd.; May 1991; 18 pages.
			"M & I Door Systems Limited" Product Brochure; M & I Door Systems Limited; Date unknown; 4 pages.
			"Rytec Breaks Away!" Products Brochures; Rytec Corporation; 1992; 2 pages.
			"Rapid Roll Doors: The Super-Fast Solution!" Products Brochure; Albany International; 1990; 8 pages.
			"Marathon Spirit" Products Brochure; Marathon Door Division - ASI Technologies; 1991; 3 pages
			"RT Series" Product Brochure; Kelley Company, Inc. 1993; 2 pages.
			"Kelley Door Selection Guide"; Kelley Company, Inc.; 1993; 16 pages

		"Speedor" Product Brochure;
		Hart;
		Date unknown 1 page



This page blank (uspto)

FILING RECEIPT

12/03/98



UNITED STATES DEPARTMENT OF COMMERCE
Patent and Trademark Office
ASSISTANT SECRETARY AND COMMISSIONER
OF PATENTS AND TRADEMARKS
Washington, D.C. 20231

APPLICATION NUMBER	FILING DATE	GRP ART UNIT	FIL FEE REC'D	ATTORNEY DOCKET NO.	DRWGS	TOT CL	IND CL
09/205,318	12/04/98	3623	\$1,042.00	97-060A	5	27	3

MATHEW C MCNEILL
RITE-HITE HOLDING CORPORATION
8900 NORTH ARBON
MILWAUKEE WI 53223

Receipt is acknowledged of this nonprovisional Patent Application. It will be considered in its order and you will be notified as to the results of the examination. Be sure to provide the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION when inquiring about this application. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please write to the Application Processing Division's Customer Correction Branch within 10 days of receipt. Please provide a copy of the Filing Receipt with the changes noted thereon.

Applicant(s)

LEPAGE QUEBEC QUEBEC
ROBERT LAPAGE, QUEBAC, CANADA; MICHEL PARADIS, QUEBAC,
CANADA.

CONTINUING DATA AS CLAIMED BY APPLICANT-

THIS APPLN IS A RE OF 08/339,175 11/10/94 PAT 5,579,820

TITLE

ROLL-UP DOOR FOR VEHICLE SHELTERS

PRELIMINARY CLASS: 160